DEKO FG

42 dB*


SOUND *up to

26 ------ DEKO FG

FULL DAYLIGHT WITH AN ELEGANT 99.9% GLAZED PARTITION

THICKNESS





PROPERTIES

• Standard sizes and individual glazed modules

DEKO FG ------ 29

- Several joint options
- A wide choice of door types with sound classifications, designs and sizes
- Specially designed, stable DEKO FG aluminium frame system for doors
- A selection of different types and thicknesses of glass
- Safety glass
- Applied graphics available
- Easy to maintain
- Sound tested
- CE-marked as a partition system
- Fully relocatable and reusable
- Indoor climate labelled
- Prefabricated
- Sound reduction of up to 42 dB
- 30 or 40 mm profile in the same design as other DEKO FG partitions
- Several types of doors



32 ------ DEKO FG

SEVERAL GLASS OPTIONS

The thickness and type of glass can be adapted as required, for example in relation to partition height, safety or sound reduction requirements.

- SLIM PROFILE STRUCTURE

maximise the flow of light and are so narrow that they almost disappear in the overall look. Profiles can be incorporated into the adjacent structure if an invisible joint is desired. All visible aluminium profiles are available as standard in natural anodised aluminium or powder coated in many colours.

Minimalist architectural design

The simple, clean lines of DEKO FG make it one of the most widely used products in many buildings.

34 ------ DEKO FG



0.7


DEKO FG WITH NATURAL ANODISED PROFILES

DEKO FG WITH CONCEALED PROFILES IN THE PARTITION



DEKO FG WITH BLACK POWDER COATED PROFILES

DEKO FG WITH CURVED GLASS



DEKO FG ------ 35

36 ------ DEKO FG

DEKO FG ------ 37

RANGE OF DOORS FOR DEKO FG





DEKO FD - FULLY GLAZED DOOR WITH ACOUSTIC STRIP



DEKO FD - FULLY GLAZED FRAMELESS SLIDING DOOR, TOP HUNG

DEKO TD - SOLID TIMBER DOOR





DEKO FD - FULLY GLAZED FRAMELESS DOOR, PIVOT-HINGED




DEKO TD - SOLID TIMBER DOOR WITH OVERHEAD PANEL


38 ----- DEKO FO

TYPE SUMMARY

Product	Sound insulation (Rw)	Partition thickness (mm)	Glass thickness (mm)	Glazed panels	Weight (kg/m²)	Fire resistance (min)
DEKO FG Profile 1	34 - 40 dB ²	27	10, 12	1	25 · 35	-
DEKO FG Profile 1	36 - 42 dB ²				38 · 43	
DEKO FG Clear ¹	34 - 40 dB ²	27	10, 12	1	25 · 35	-
DEKO FG Clear ¹	36 - 42 dB ²	30 · 32	15, 17	1	38 · 43	-

DETAILS






WALL CONNECTION


DEKO FG ------ 39


WALL CONNECTION





JOINT 1) DEKO FG CLEAR 2) DEKO FG PROFILE 90° CORNER JOINT 1) DEKO FG CLEAR 2) DEKO FG PROFILE T-JOINT 1) DEKO FG CLEAR 2) DEKO FG PROFILE







DEKO TD - SOLID TIMBER DOOR

DEKO FD - FULLY GLAZED DOOR

DEKO DG - DOUBLE GLAZED DOOR

n any gate operations are expended on a sets and obtained of an one project. For more more momentation about maximum a odules, choice of glass types and joints, contact the local distributor or DEKO. I Sound reduction value for the glass itself depends on the type of glass that is incorporated.

For updated values and details, please visit deko.com

