DEKO FG FIRE

51 dB*

SOUND *up to

FIRE-CLASSIFIED FULLY GLAZED PARTITION


Designed, engineered and certified to the latest European safety standards, DEKO FG Fire ensures safety from fire and smoke. This impressive product is in high demand due to its cost effectiveness, minimal detailing and high performance levels - including an acoustic performance of up to 51 dB.

DEKO FG Fire comprises a single glazed, full height panel finished with narrow profiles at all interfaces with the existing interior. The vertical joints between the glazed panels are fireproof and available in three different designs: Profile, Clear or Black.

DEKO FG Fire can be double glazed to achieve barrier loadings (guarding) and even higher acoustic performance where required.

> EI 120* Fire *up to







PROPERTIES

• Fire approved in slim profile structure


DEKO FG Fire ----- 77


- Several variations for glass joints as other DEKO FG fully glazed partitions
- 30 or 40mm profile in design like other DEKO glazed partitions
- Fire approved up to El 120 A2-s1, d0
- Sound reduction up to 51dB
- Fire tested up to 3.5m
- Multiple colours of profiles
- Elegant aluminium profiles
- Several door types
- Fire-tested special solution for motion absorption
- Several glass types
- Safety glass
- Reusable
- Prefabricated
- Applied graphics available

FULLY GLAZED PARTITION Maximum safety and visibility with minimal detailing


Fully glazed partition with one layer of fire-rated glass of 16-48mm, depending on fire and sound requirements. The glass provides up to 51 dB of sound reduction depending on the type of glass. The fire-classified partition is part of a fire-approved partition system with an elegant aluminium structure, classified up to El 120 with narrow profiles, whatever the fire requirements.

Whatever the fire and glass joint requirements, we use the same narrow 30 or 40mm patented profile structure in the edge of the glazed partition. If you want DEKO FG Fire Profile, it is the same narrow profile in a vertical joint and the same design line.





82 ----- DEKO FG Fire







DEKO FG FIRE BLACK



DEKO FG FIRE CLEAR

DEKO FG Fire ----- 83

84 ----- DEKO FG Fire

DEKO FG Fire ----- 85

RANGE OF DOORS FOR DEKO FG FIRE



DEKO TD - SOLID TIMBER DOOR



DEKO AG - ALUMINIUM GLASS FRAMED DOOR



DEKO FD - FULLY GLAZED FRAMELESS DOOR, PIVOT-HINGED



DEKO TG - GLASS FRAMED TIMBER DOOR

86 ----- DEKO FG Fir

TYPE SUMMARY

Product	Fire resistance (min)	Sound insulation (Rw)	Partition thickness (mm)	Glass thickness (mm)	Glazed panels	Weight (kg/m²)
DEKO FG Fire Profile 1	E 30	32 - 38 dB ²	19 - 25	6 - 12mm fire-rated glass	1	15 - 30
DEKO FG Fire Profile 1	EW 30 ³	37 - 40 dB ²	24 - 35	11 - 22mm fire-rated glass		25 - 49
DEKO FG Fire Profile 1	EW 60 ³	37 - 40 dB ²	24 - 35	11 - 22mm fire-rated glass		
DEKO FG Fire Profile ¹	EW 90 ³	37 - 40 dB ²	24 - 35	11 - 22mm fire-rated glass		25 - 49
DEKO FG Fire Profile ¹	EW 120 ³	37 - 40 dB ²	24 - 35	11 - 22mm fire-rated glass	1	25 - 49
DEKO FG Fire Profile 1	EI 30	38 - 40 dB ²	29 - 31	16 - 18mm fire-rated glass	1	34 - 39
DEKO FG Fire Profile ¹	EI 60	41 - 44 dB ²	38 - 46	25 - 33mm fire-rated glass	1	52 - 73
DEKO FG Fire Profile ¹	EI 90	46 dB ²	53 - 61	40 - 48mm fire-rated glass	1	82 - 102
DEKO FG Fire Profile ¹	EI 120	46 dB ²	53 - 61	40 - 48mm fire-rated glass	1	82 - 102
DEKO FG Fire Black ¹	EW 30 ³	39 dB ²		20mm fire-rated glass		
DEKO FG Fire Black 1	EW 60 ³	39 - 43 dB ²		20 - 30mm fire-rated glass		
DEKO FG Fire Black ¹	EI 30	39 - 43 dB ²		20 - 30mm fire-rated glass		
DEKO FG Fire Black ¹	EI 45	41 - 43 dB ²	36 - 43	23 - 30mm fire-rated glass	1	52 - 69
DEKO FG Fire Black ¹	EI 60	40 - 44 dB ²	44 - 54	31 - 41mm fire-rated glass	1	69 - 94
DEKO FG Fire Clear ¹	EW 30 ³	39 dB ²	30 - 37	17 - 24mm fire-rated glass		40 - 56
DEKO FG Fire Clear ¹	EI 30	39 dB ²		17 - 24mm fire-rated glass		
DEKO FG Fire Clear ¹	EI 45	40 - 43 dB ²	39 - 47	26 - 34mm fire-rated glass		
DEKO FG Fire Clear ¹	EI 60	40 - 43 dB ²	39 - 47	26 - 34mm fire-rated glass		

 Fully glazed partitions are available in sizes and modules to suit the project. For more information about maximum size modules, choice of glass types and joints, contact the local distributor or DEKO.
Sound reduction value for the glass itself depends on the type of glass that is incorporated.
EW also meets fire classification E

For updated values and details, please visit deko.com

DETAILS







DEKO FG Fire ----- 87


CEILING CONNECTION

FLOOR CONNECTION


WALL CONNECTION







JOINT DEKO FG FIRE PROFILE JOINT DEKO FG FIRE BLACK JOINT DEKO FG FIRE CLEAR



DEKO AG - ALUMINIUM GLASS FRAMED DOOR

DEKO FG FIRE Profile EI 30 and EI 60 with special features are fire tested to accommodate movements at the top of the partition and by the floor.